

# ResPlus BiPap Machine



## Superior performance by design

- Patient Ventilator Synchrony: Synchronised patient trigger ensures breathing comfort
- Dynamic monitoring with real-time display of: Waveforms and breathing data that monitors therapy outcomes
- Intelligent Operation Interface: 3.5" Colour TFT Display Concise interface, rotary parameter selection dial, simple and easy to operate, HD colour display
- VAF Intelligent Tidal Volume Control: Ensure target tidal volume meets the needs of different patients
- Ultra quiet operating mode <30db ensures comfort during sleep
- Detachable humidifier: Provides variable humidity settings, removable chamber for ease of cleaning
- Automatic Leakage Compensation: Detects the difference in flow rate when the user turns over at night, automatic compensation of the leakage volume, safer and more effective

Part Number	PHB-30T	PHB-30P
Respiratory Mode	CPAP, S/T, S, T	CPAP, S/T, S, T, APCV
Parameters		
IPAP	4-30cmH2O	4-30cmH2O
EPAP	4-25cmH2O	4-25cmH2O
Isens	Auto, 1-6 level	Auto, 1-6 level
Esens	Auto, 1-6 level	Auto, 1-6 level
Islop	1-6 level	1-6 level
Insp Time	0.5-4s	0.5-4s
Max Insp Time	0.5-4s	0.5-4s
Min Insp Time	0.5-4s	0.5-4s
BPM	3-40bpm	3-40bpm
VAF settings	-	Available
Target VT	-	50-2000ml
Ramp	0-60min	0-60min
Auto-on	On/Off	On/Off
Auto-off	On/Off	On/Off
Auto air compensation	Available	Available
Auto adjustment altitude	Available	Available
Noise Level	≤30dBA	≤30dBA
Humidifier	0-5 level	0-5 level
Weight	2.2kg	2.2kg
Data Storage	TF Card	TF Card
Screen	3.5" Colourful LCD	3.5" Colourful LCD
SPO2 Kit	Optional	Optional

